

► TECHNICAL SPECIFICATIONS

Filter Media	Minipleat Micro Glass Fibre
Frame Material	Plastic
Header Thickness	25 mm
Classification (1822)	E10 - E17
Gasket	Optional (Polyurethane / Epdm)
Seperator	Hot-melt
Sealant	2K Polyurethane
Final Pressure Drop	600 Pa
Max. Temperature	80°C
Max. Humidity	90%



PRODUCT CODE	CLASS EN1822	WIDTH (mm)	HEIGHT (mm)	DEPTH (mm)	FILTRATION AREA (m²)	NOMINAL AIR FLOW (m³/h)	INITIAL PRESSURE DROP (± 10 % Pa)
FC-E10-H-01	E10	287	592	292	9	1700	170
FC-E10-H-02	E10	490	592	292	15	2800	170
FC-E10-H-03	E10	592	592	292	18	3400	170
FC-E11-H-01	E11	287	592	292	9	1700	190
FC-E11-H-02	E11	490	592	292	15	2800	190
FC-E11-H-03	E11	592	592	292	18	3400	190
FC-E12-H-01	E12	287	592	292	9	1700	210
FC-E12-H-02	E12	490	592	292	15	2800	210
FC-E12-H-03	E12	592	592	292	18	3400	210
FC-H13-H-01	H13	287	592	292	9	1700	250
FC-H13-H-02	H13	490	592	292	15	2800	250
FC-H13-H-03	H13	592	592	292	18	3400	250