

HOODED TYPE FILTER



► TECHNICAL SPECIFICATIONS

Filter Media	Minipleat Micro Glass Fibre
Frame Material	Extruded Aluminium
Classification (EN779:2012)	E10-U17
Gasket	Optional (Polyurethane/EPDM)
Seperator	Hot-melt
Sealant	2K Polyurethane
Final Pressure Drop	600 Pa
Max. Temperature	80°C
Max. Humidity	90%



PRODUCT CODE	CLASS (EN779:2012)	WIDTH (mm)	HEIGHT (mm)	DEPTH (mm)	SPIG OUT DIAMETER (mm)	FILTRATION AREA (m²)	NOMINAL AIR FLOW (m³/h)	INITIAL PRESSURE DROP (± 10 % Pa)
FHH-H13-01	H13	305	305	125	Ø125	2,45	150	100
FHH-H13-02	H13	305	610	125	Ø150	4,9	300	100
FHH-H13-03	H13	457	457	125	Ø150	5,5	340	100
FHH-H13-04	H13	535	535	125	Ø200	7,55	465	100
FHH-H13-05	H13	575	575	125	Ø200	8,7	535	100
FHH-H13-06	H13	610	610	125	Ø200	9,8	600	100
FHH-H13-07	H13	610	762	125	Ø250	12,25	750	100
FHH-H13-08	H13	610	915	125	Ø250	14,7	900	100
FHH-H13-09	H13	610	1220	125	Ø250	19,6	1200	100
FHH-H14-01	H14	305	305	125	Ø125	2,45	150	125
FHH-H14-02	H14	305	610	125	Ø150	4,9	300	125
FHH-H14-03	H14	457	457	125	Ø150	5,5	340	125
FHH-H14-04	H14	535	535	125	Ø200	7,55	465	125
FHH-H14-05	H14	575	575	125	Ø200	8,7	535	125
FHH-H14-06	H14	610	610	125	Ø200	9,8	600	125
FHH-H14-07	H14	610	762	125	Ø250	12,25	750	125
FHH-H14-08	H14	610	915	125	Ø250	14,7	900	125
FHH-H14-09	H14	610	1220	125	Ø250	19,6	1200	125